

Adjusted by:
 E-mail:
 Adjusted for:

Tel:
 Date:

Total weight (g):

The weight changes based on the choices made below.

S3 Swing has divided, swing away leg support and an adjustable rear axle in carbon fibre. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". S3 Swing has a seat height of 45cm in front and 43 cm at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from the List of options.

Max userweight: 100 kg for seat width 33-42.

Save the guide to the "desktop" and open it with [Adobe Reader](#), for best function Design your wheelchair by clicking in the circles in this guide. Blue, underlined text is clickable to [show info](#) or image. BB = seatwidth, HH= backrest height

Original design

Alternative options

Other options

[info](#)

1) Chassis colour

- Black - Anodic Black
- Clear

- Optional colour - A higher price and longer delivery time for optional colour

Optional colour



2) Seat width (BB)

- 33 cm
- 36 cm
- 39 cm
- Clear

Art.no include: chassis, seat, calf strap, backrest lock



3) Back rest

- S3 standard 523BBHH VER2
- Clear

Height (HH)

- 20 cm
- 25 cm
- 30 cm
- 35 cm
- 40 cm
- 45 cm
- Clear

- Tapered 525BBHH VER2
- Curved back 524BBHH VER2

- Other back rest

List of options art.



4) Rear axle

- Carbon standard 33023BB
- Clear

- Carbon +15 mm 33023BC*

* seat width BB +1

Use this rear axle when choosing arm support at Accessories and/or increased seat height

- Other rear axle or seat height

Increase seat height

List of options art.



5) Castor and fork

- 120 mm art.no.
- Clear

- 90 mm art.no.
- 150 mm art.no.



6) Footrest

- Swing S3 cpl pair art.no.
- Clear

- Foot plate large, extended 50mm_forward art.no.

- Extended tubes 40 mm art.no.
- Heel straps for footplates art.no.



7) Brake

- Brake S3 4630000
- Clear



8) Rear wheel - without pushrim

- 22" Standard art.no.
- Clear

- 24" Standard art.no.

Rear wheel sizes

NOTE! Rear axle position only in 0 mm with 24" rear wheels.

- Other rear wheel

List of options art.



Tire - choose tire

- Schwalbe Right Run 22", 24"
- Clear

- Rugged 24"
- Schwalbe Marathon Plus 24"

- PU 24" (massive)



9) Pushrim

- Titanium 190DD11 (x2 / wheelchair)
- Clear

DD = Wheel diameter

- Paragrip 19051DDBT x2
- Tetragrip 19052DDBT x2

- Maxgrip 22", 24" (contains latex) 1903060 x2 (60=24", 80=22")
- Aluminum 24" 1904404 x2

Accessories



Side guard S3

- [Side guard S3](#) [Video](#)
[art.no.](#)
- Clear



Arm support

- [Arm support S3](#) [Video](#)
[art.no.](#)



Side guard Carbon

- [Side guard Carbon](#)
[art.no.](#)



Push handles

- [Height adjustable S3](#) [Video](#)
4252060 VER2
- [Height adjustable S3 +10](#)
4252063 VER2
- Clear Max. userweight 100kg



Push handle Foldable

- [Foldable S3](#) [Video](#)
4245000



Push bar

- [Push bar S3](#)
42400BB VER2
Max. userweight 100kg



Anti-tip


- [Anti-tip](#) std seat height
4353000 [Video](#)

[Other seat height](#)



Cushion Wedge cushion

- [2,5 cm](#)
572BB35
- [5 cm](#)
575BB35
- Clear
- [Wedge cushion](#)
57710BB



Spoke protectors

- [24" Panthera logo](#)
4500000
- [24" without logo](#)
4500011
- Clear



Other

- [Tube protection front](#)
9900251 (2 pcs)
- [Tube protection rear](#)
9900251 (1 pcs)
- [Crutch holder S3](#) _____ pcs
9900301 (x1/crutch)
- [Backrest wedge](#) _____ pcs
4710012

Set-up adjustments



Backrest angle

Note measure (A) for desired back rest angle.
14-28 mm. Standard=18 mm

A= _____ mm



Rear axle adjustment

Note measure (A) for desired balance.
Standard=25 mm

A= _____ mm



Footrest height

Note measure (A) and (B) for the footrest.

A= _____ mm B= _____ mm



Transportation marking

- YES do mark the wheelchair with attachment points for transport in disabled service vehicle.

NOTE! See [manual](#) for more information.

Extra