

Adjusted by:

E-mail:

Adjusted for:

Tel:

Date:

Total weight (g):

The weight changes based on the choices made below.

S3 Swing Low 0° has divided, swing away leg support and an adjustable rear axle in carbon fibre. To find a balance that suits you the rear axle can be adjusted into different positions. Note desired measure at "Settings". S3 Swing Low 0° has a seat height of 39cm in front and 39 cm at the rear, without cushion. To adjust the seat height you can chose other rearwheel sizes or a raising Kit with suitable castor fork from the List of options.
Max userweight: 100 kg for seat width 36-42 and 150kg for seat width 45-50 cm.

Save the guide to the "desktop" and open it with [Adobe Reader](#), for best function Design your wheelchair by clicking in the circles in this guide. Blue, underlined text is clickable to [show info](#) or image. **BB** = seatwidth, **HH**= backrest height

Original design

Alternative options

Other options

[info](#)



1) [Chassis colour](#) Click on the link to see up-to-date colours



2) [Seat width \(BB\)](#) 36 cm 39 cm 42 cm 45 cm 50 cm

Art.no include: chassis, seat, backrest lock

3) [Seat depth](#) 35 cm 40 cm
 Clear

37,5 cm



4) [Back rest](#) Standard 523BBHH VER2
 Clear

Height (HH) 20 cm 35 cm 25 cm 40 cm 30 cm 45 cm
 Clear

[Tapered](#) 525BBHH VER2
 [Curved back](#) 524BBHH VER2
 With backward curving the anti-tip device is complemented with "Knob anti-tip device S3 low profile", art.no. 4353121

[Back rest, extended range](#)
 [Frame for fixed backrest systems](#)
 With backward curving the anti-tip device is complement with "Knob anti-tip device S3 low profile", art.no. 4353121
 art. _____



5) [Rear axle](#) Carbon standard 33023BB
 Clear

[Carbon +15 mm](#) 33023BC*
 * seat width BB +1
 Use this rear axle when chosing arm support at Accessories and/or increased seat height

Other seat height
[Increase seat height](#)
 The older rearaxle is not possible to mount.



6) [Castor and fork](#) 120 mm
 Clear

90 mm



7) [Footrest](#) Swing S3 cpl pair art.no.
 Clear

[Footplate large](#) art.no.

[Heel straps for footplates](#) art.no.



8) [Brake](#) Brake S3 4630000
 Clear

Other brake
 Assistant brake is not possible to mount.



9) [Rear wheel - without pushrim](#) 24" Standard art.no.
 Clear

22" Standard [Rear wheel sizes art.no.](#)

Other rear wheel
 One arm drive is not possible to mount.



[Tire - choose tire](#) Right Run 22",24" Standard
 Rensa

Rugged 24"
 Marathon Plus 22", 24",25",26"

PU 24" (massive)
 PU 22" (massive)



10) [Pushrim](#) Titanium 190DD11 (x2)
 Rensa **DD** = Hjulldiameter

Paragrip 19051DDBT x2
 Tetragrip 19052DDBTx2
DD = Hjulldiameter

Maxgrip 24" (contains latex) 1903060 x2
 Maxgrip 22" (contains latex) 1903080 x2

Accessories



Side guard S3

- [Side guard S3 Video](#)
[art.no.](#)
[Info](#)

Clear



Arm support

- [Arm support S3 Video](#)
[art.no.](#)

Only Arm support for 26" can be used.



Side guard Carbon

- [Carbon](#)
[art.no.](#)
- [Carbon,small cover](#)
[art.no.](#)
- [Carbon,large cover *](#)
[art.no.](#)

* Only with one arm brake



Push handles H/S

- [Height adjustable S3 Video](#)
4252060 VER2
- [Height adjustable S3+10 cm](#)
4252063 VER2
Max. userweight 100kg
- Clear



Push handle Foldable

- [Foldable S3 Video](#)
4245000



Push bar

- [Push bar S3](#)
42400BB VER2
Max. userweight 100kg.



Anti-tip

- [Anti-tip std seat height](#)
4353000 [Video](#)

[Other seat height](#)



Cushion

Seat depth 35 cm Seat depth 40 cm

- [2,5 cm](#) [2,5 cm](#)
572BB35 572BB40
- [5 cm](#) [5 cm](#)
575BB35 575BB40
- Clear




Spoke protectors

- [24" logo](#) [22" logo](#)
4500000 4500100
- [24" no logo](#) [22" no logo](#)
4500011 4500111
- Clear



Other

- [Tube protection](#) _____ p
- 9900251 (x3/wheelchair)
- [Crutch holder S3](#) _____ p
- 9900301 (x1/crutch) [Video](#)
- [Back rest wedge](#) _____ p
- 4710012



Wedge cushion

- [Wedge cushion](#)
57710BB

Set-up adjustments



Backrest angle

Ange måttet (A) för önskad ryggvinkel.
14-28 mm. Standard=18 mm

A= _____ mm



Rear axle adjustment

Ange måttet (A) för önskad balansering.
Standard=40 mm

A= _____ mm



Footrest height

Note measure (A) and (B) for the footrest.

A= _____ mm B= _____ mm

Transportation marking

- YES do mark the wheelchair with attachment points for transport in disabled service vehicle.

Art.no.9000152

NOTE! See [manual](#) for more information.

Extra