Orderguide Panthera X

Save the guide to the desktop and open it from there.

art.nr. guide-X-eng
rev.2019-02

Adjusted by: | Tel:
E-mail: | Date:
Adjusted for:

Total weight (g): 0

The weight changes based on the choices made below.

Panthera X has the chassis and backrest made in carbon fibre and a rigid rear axle.
The balance is adjusted by positioning the backrest in **4 different positions**.
Panthera X is delivered without anti-tip device and is intended for advanced users only.
Max user weight is **100 kg for seat width 33-45 cm**.

Save the guide to the "desktop" and open it with **Adobe Reader., for best function**
Design your wheelchair by clicking in the circles in this guide.
Blue, underlined text is clickable to show info or image.
BB = seatwidth, **HH**= backrest height

Original design	Alternative options	Other options	info

1) Seat width (BB) Chassis art.no.

○ 33 cm ○ 36 cm ○ 39 cm ○ 42 cm ○ 45 cm

◉ Clear

2) Backrest height 22-35 cm (HH) art.no.

○ 22 cm ○ 23 cm ○ 24 cm ○ 25 cm ○ 26 cm ○ 27 cm ○ 28 cm
○ 29 cm ○ 30 cm ○ 31 cm ○ 32 cm ○ 33 cm ○ 34 cm ○ 35 cm

◉ Clear

3) Balance info

○ **Position 1** **Most** easy balanced
○ **Position 2** Less easy balanced
○ **Position 3** Medium balanced
○ **Position 4** Least easy balanced

◉ Clear

The positioning of the backrest on the chassis affects the balance / COG of the wheelchair. "easy balanced" = easy to practice rear wheel balance. This can later easily be changed.

4) Castor art.no.

○ 3" X (87 mm)

◉ Clear

○ 90 mm S3 art.no.

5) Footrest

○ Footrest Alu X
36004 BB

◉ Clear

○ Footrest Titanium
36915BB
○ Footrest Titanium, extended, reinforced
36006BB needed for Freewheel
○ Plastic plate for foot bow
36010BB

7) Brake art.no.

○ One hand brake, right

◉ Clear

○ One hand brake, left

8) Rear wheel - without pushrim

○ 24" Spinergy X black spokes
○ 24" Spinergy X white spokes

art.no.

◉ Clear

○ 25" Spinergy X black spokes
○ 25" Spinergy X white spokes
○ 26" Spinergy X black spokes
○ 26" Spinergy X white spokes

Rear wheel sizes

Tire - choose tire

○ Schwalbe One 24", 25"

◉ Clear

○ Right Run 24",25",26"
○ Marathon Plus 24",25",26"

○ Rugged 24"

10) Push rim

○ Aluminum X
1904404 (5) (6) (x2) 24" (25") (26")

◉ Clear

○ Titanium
190DD11 x2
○ Paragrip
19051DDBTx2
○ Tetragrip
19052DDBTx2

DD = Wheel diameter in inches

○ Maxgrip 24" (contains latex)
1903060 x2

Accessories

Side guard

- ○ Carbon — info — desired art
  article number
- ◉ Clear

Side guard

- ○ Carbon, small cover
  art.no.

Side guard

- ○ Carbon, large cover
  art.no.

Cushion — Wedge cushion

- ○ X 5 cm
  47501BB
  seat depth 40 cm
- ◉ Clear
- ○ Wedge cushion
  57710BB





Arm hook

- ○ Arm hook X
  4200010
- ◉ Clear



Transport protection

- ○ Housing
  9024009
- ○ Rear end
  9024012
- ○ Rear axle
  9024008

Other

- ○ Freewheel info
  2600102
- ○ Tube protection front
  9900252 (2 pcs)
- ○ Tube protection rear
  _9900252 (1 pcs)

Set-up adjustments

Backrest angle

Note measure (A) for desired back rest angle
10-20 mm. Standard=15 mm

A=_____ mm

Footrest height

Note measure (A) for desired footrest height
Standard = 70 mm

A=_____ mm

Extra

Panthera AB, Gunnebogatan 26, 163 53 Spånga, Sweden - Tel:+46-8-761 50 40, Fax: +46-8-621 08 10, panthera@panthera.se, www.panthera.se