

Victory® 10 DX

SUPREME PERFORMANCE,
EXHILERATING STYLE,
AND EXCELLENT VALUE.

VICTORY® 10 DX


The sleek, sporty Victory® 10 DX scooter delivers smooth performance and all-new features. With a full complement of advanced standard features including, rugged suspension, high-visibility automatic front and rear lighting system, feather-touch disassembly, LED kerb light, and wraparound delta tiller, the Victory® 10 DX is a greater value than ever before.



Victory® 10 DX

Weight capacity:	159 kg
Maximum speed ¹ :	Up to 8.5 km/h
Ground clearance ² :	3.5 cm
Turning radius:	137.16 cm
Overall length ² :	118.75 cm
Overall width ² :	56.5 cm
Front tyres:	9 cm x 25 cm
Rear tyres:	10 cm x 25 cm
Suspension:	Front and rear
Range per charge ¹ :	Up to 40 km
Maximum obstacle climbing ability:	5 cm
Total Weight Without Batteries:	63.5 kg
Heaviest piece when disassembled:	32 kg
Standard seating:	Type: CRS Junior seat Weight: N/A Material: Gray Vinyl Dimensions: width – n/a depth – n/a
Drive System:	Rear-wheel drive, sealed transaxle, 24-volt DC motor
Dual Braking System:	Electronic, regenerative, and electromechanical
Battery Requirements ³ :	Two 12-volt, deep cycle Size: U-1 or optional 40 AH Weight: U-1 : 11 kg each; 40 AH : 15 kg each
Battery Charger:	3-amp, off-board with U-1 batteries 5-amp, off-board with optional 40 AH batteries

Colors:



¹Varies with user weight, terrain type, battery amp-hour (AH), battery charge, battery condition and tyre condition.

²Due to manufacturing tolerances and continual product improvement, this specification can be subject to a variance of (+ or - 3%).

³AGM or Gel-Cell type required.

NOTE: All specifications subject to change without notice.

"The information contained herein is correct at the time of publication; due to Pride's commitment to constant improvement and development, we reserve the right to alter specifications without prior notice".

"Theoretical range is calculated under test conditions in accordance with European standards. Actual range in normal use will depend on many factors, including the condition of the vehicle and its batteries, the weight of the driver, correct tyre pressures, ambient temperature, and the gradient and surface of the road or pavement".

Features

- Front and rear suspension
- High-visibility automatic front and rear lighting system
- Exclusive one-hand feather-touch disassembly provides the ultimate quick transport system
- Long-lasting, high-intensity LED headlight, tail light and indicators
- Pride's exclusive stylish, light weight, non-marking, low profile wheels
- Auto-connecting front-to-rear harness
- Delta tiller with wrap-around handles
- New back-lit battery meter for increased accuracy and visibility in any setting
- Includes pinchless hinges & eight-position seat rotation
- Easy-grip tiller adjustment knob
- Easy access tiller-mounted charger port for standard dual voltage off-board charger
- Rear view mirror standard

Options

- Forearm crutch holder
- Cane/crutch holder
- Oxygen tank holder
- Cup holder
- Rear basket
- Safety flag
- Walker holder
- Weather cover
- Saddlebag

Castricum Werf 26
1901 RW Castricum
Netherlands

Tel: +31 251 377 577
Fax: +31 251 377 580
www.pridemobility.com



Pride[®]
Mobility Products BV